


REDEEM PLUS


LED Bulb E27 A60A 5000 K

With an average efficiency of **149 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA60A502901NN



Light Projection Diagram



D: 60 mm H: 118 mm W: 60 mm




Color Spectrum Distribution

REDEEM PLUS


LED Bulb E27 A60A 5700 K

With an average efficiency of **149 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA60A572901NN



Light Projection Diagram



D: 60 mm H: 118 mm W: 60 mm



Color Spectrum Distribution

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA60A502901NN
GTIN (EAN13)	8684216000393
Case	A60
Case Sub Type	A
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A60A 5000K
Description	Tuled Redeem Plus LED Bulb E27 A60A 5.8W 863lm 5000K Tuled White



Physical Properties	
Width (W)	60 mm
Diameter (D)	60 mm
Height (H)	118 mm
Weight	29 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	24 (carton)
Euro Pallet	2,400 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	5.8 kWh/1000hours
AC Current	57 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.44

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	2.72 W
Beam Angle	170°
Luminous Flux	863 lm
CRI	85 Ra
Lighting Efficiency	149 lm/W
Color Temperature	5000 K
Color Temperature Name	Tuled White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA60A572901NN
GTIN (EAN13)	8684216000409
Case	A60
Case Sub Type	A
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A60A 5700K
Description	Tuled Redeem Plus LED Bulb E27 A60A 5.8W 858lm 5700K Gloss White



Physical Properties	
Width (W)	60 mm
Diameter (D)	60 mm
Height (H)	118 mm
Weight	29 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	24 (carton)
Euro Pallet	2,400 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	5.8 kWh/1000hours
AC Current	57 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.44

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	2.76 W
Beam Angle	170°
Luminous Flux	858 lm
CRI	85 Ra
Lighting Efficiency	149 lm/W
Color Temperature	5700 K
Color Temperature Name	Gloss White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

REDEEM PLUS


LED Bulb E27 A60A 6500 K

With an average efficiency of **145 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA60A652901NN



Light Projection Diagram



D: 60 mm H: 118 mm W: 60 mm



Color Spectrum Distribution

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA60A652901NN
GTIN (EAN13)	8684216000416
Case	A60
Case Sub Type	A
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A60A 6500K
Description	Tuled Redeem Plus LED Bulb E27 A60A 5.8W 845lm 6500K Cool White



Physical Properties	
Width (W)	60 mm
Diameter (D)	60 mm
Height (H)	118 mm
Weight	29 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	24 (carton)
Euro Pallet	2,400 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	5.8 kWh/1000hours
AC Current	58 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.44

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	2.79 W
Beam Angle	170°
Luminous Flux	845 lm
CRI	85 Ra
Lighting Efficiency	145 lm/W
Color Temperature	6500 K
Color Temperature Name	Cool White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Equivalent	
Equivalent Incandescent Typical	65 W
Equivalent CFL	13 W
Equivalent LED Bulb	11 W
Tuled	5.8 W
Efficiency Compared to Inc.	1,017 %
Efficiency Compared to CFL	123 %
Eff. Compared to Traditional LED	77 %

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

The technical data was obtained under 25°C, 230V, and 50Hz test conditions.
Technical data may vary depending on the conditions.




Human-Nature-Budget

REDEEM PLUS


LED Bulb E27 A70S 2700 K

With an average efficiency of **135 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA70S272122NN



Light Projection Diagram



D: 70 mm H: 134 mm W: 70 mm




Color Spectrum Distribution

REDEEM PLUS


LED Bulb E27 A70S 3000 K

With an average efficiency of **141 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA70S302132NN



Light Projection Diagram



D: 70 mm H: 134 mm W: 70 mm



Color Spectrum Distribution

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA70S272122NN
GTIN (EAN13)	8684216000768
Case	A70
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A70S 2700K
Description	Tuled Redeem Plus LED Bulb E27 A70S 8.8W 1183lm 2700K Warm White



Physical Properties	
Width (W)	70 mm
Diameter (D)	70 mm
Height (H)	134 mm
Weight	38 g/unit
IP Class	IP50
Carton	80 (pcs)
Euro Pallet	12 (carton)
Euro Pallet	960 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	E (A-G)
Yearly Consumption	8.8 kWh/1000hours
AC Current	80 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.48

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	3.70 W
Beam Angle	160°
Luminous Flux	1,183 lm
CRI	85 Ra
Lighting Efficiency	135 lm/W
Color Temperature	2700 K
Color Temperature Name	Warm White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA70S302132NN
GTIN (EAN13)	8684216000775
Case	A70
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A70S 3000K
Description	Tuled Redeem Plus LED Bulb E27 A70S 8.9W 1258lm 3000K Mild White



Physical Properties	
Width (W)	70 mm
Diameter (D)	70 mm
Height (H)	134 mm
Weight	38 g/unit
IP Class	IP50
Carton	80 (pcs)
Euro Pallet	12 (carton)
Euro Pallet	960 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	8.9 kWh/1000hours
AC Current	81 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.48

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	3.87 W
Beam Angle	160°
Luminous Flux	1,258 lm
CRI	85 Ra
Lighting Efficiency	141 lm/W
Color Temperature	3000 K
Color Temperature Name	Mild White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

REDEEM PLUS


LED Bulb E27 A70S 3500 K

With an average efficiency of **141 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA70S352132NN



Light Projection Diagram



D: 70 mm H: 134 mm W: 70 mm




Color Spectrum Distribution

REDEEM PLUS


LED Bulb E27 A70S 4000 K

With an average efficiency of **146 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA70S402132NN



Light Projection Diagram



D: 70 mm H: 134 mm W: 70 mm



Color Spectrum Distribution

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA70S352132NN
GTIN (EAN13)	8684216000782
Case	A70
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A70S 3500K
Description	Tuled Redeem Plus LED Bulb E27 A70S 8.9W 1262lm 3500K Soft White



Physical Properties	
Width (W)	70 mm
Diameter (D)	70 mm
Height (H)	134 mm
Weight	38 g/unit
IP Class	IP50
Carton	80 (pcs)
Euro Pallet	12 (carton)
Euro Pallet	960 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	8.9 kWh/1000hours
AC Current	81 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.48

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	3.86 W
Beam Angle	160°
Luminous Flux	1,262 lm
CRI	85 Ra
Lighting Efficiency	141 lm/W
Color Temperature	3500 K
Color Temperature Name	Soft White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA70S402132NN
GTIN (EAN13)	8684216000799
Case	A70
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A70S 4000K
Description	Tuled Redeem Plus LED Bulb E27 A70S 8.9W 1296lm 4000K Natural White



Physical Properties	
Width (W)	70 mm
Diameter (D)	70 mm
Height (H)	134 mm
Weight	38 g/unit
IP Class	IP50
Carton	80 (pcs)
Euro Pallet	12 (carton)
Euro Pallet	960 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	8.9 kWh/1000hours
AC Current	80 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.48

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	3.97 W
Beam Angle	160°
Luminous Flux	1,296 lm
CRI	85 Ra
Lighting Efficiency	146 lm/W
Color Temperature	4000 K
Color Temperature Name	Natural White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

REDEEM PLUS


LED Bulb E27 A70S 5000 K

With an average efficiency of **146 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA70S502132NN



Light Projection Diagram



D: 70 mm H: 134 mm W: 70 mm




Color Spectrum Distribution

REDEEM PLUS


LED Bulb E27 A70S 5700 K

With an average efficiency of **145 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA70S572132NN



Light Projection Diagram



D: 70 mm H: 134 mm W: 70 mm



Color Spectrum Distribution

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA70S502132NN
GTIN (EAN13)	8684216000805
Case	A70
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A70S 5000K
Description	Tuled Redeem Plus LED Bulb E27 A70S 9.1W 1322lm 5000K Tuled White



Physical Properties	
Width (W)	70 mm
Diameter (D)	70 mm
Height (H)	134 mm
Weight	38 g/unit
IP Class	IP50
Carton	80 (pcs)
Euro Pallet	12 (carton)
Euro Pallet	960 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	9.1 kWh/1000hours
AC Current	82 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.48

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	4.17 W
Beam Angle	160°
Luminous Flux	1,322 lm
CRI	85 Ra
Lighting Efficiency	146 lm/W
Color Temperature	5000 K
Color Temperature Name	Tuled White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA70S572132NN
GTIN (EAN13)	8684216000812
Case	A70
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A70S 5700K
Description	Tuled Redeem Plus LED Bulb E27 A70S 8.9W 1296lm 5700K Gloss White



Physical Properties	
Width (W)	70 mm
Diameter (D)	70 mm
Height (H)	134 mm
Weight	38 g/unit
IP Class	IP50
Carton	80 (pcs)
Euro Pallet	12 (carton)
Euro Pallet	960 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	8.9 kWh/1000hours
AC Current	79 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.49

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	4.18 W
Beam Angle	160°
Luminous Flux	1,296 lm
CRI	85 Ra
Lighting Efficiency	145 lm/W
Color Temperature	5700 K
Color Temperature Name	Gloss White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

REDEEM PLUS


LED Bulb E27 A70S 6500 K

With an average efficiency of **144 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA70S652132NN



Light Projection Diagram



D: 70 mm H: 134 mm W: 70 mm



Color Spectrum Distribution

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA70S652132NN
GTIN (EAN13)	8684216000829
Case	A70
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A70S 6500K
Description	Tuled Redeem Plus LED Bulb E27 A70S 8.9W 1279lm 6500K Cool White



Physical Properties

Width (W)	70 mm
Diameter (D)	70 mm
Height (H)	134 mm
Weight	38 g/unit
IP Class	IP50
Carton	80 (pcs)
Euro Pallet	12 (carton)
Euro Pallet	960 (pcs)

Light Characteristic

Declared Radiant Power	4.23 W
Beam Angle	160°
Luminous Flux	1,279 lm
CRI	85 Ra
Lighting Efficiency	144 lm/W
Color Temperature	6500 K
Color Temperature Name	Cool White

Thermal Characer

Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

Electrical Characteristic

Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	8.9 kWh/1000hours
AC Current	80 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.48

Production Composition

Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime

Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions

Dimmable	No
----------	----

Environmental Features

RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Equivalent

Equivalent Incandescent Typical	100 W
Equivalent CFL	20 W
Equivalent LED Bulb	16 W
Tuled	8.9 W
Efficiency Compared to Inc.	1,009 %
Efficiency Compared to CFL	122 %
Eff. Compared to Traditional LED	76 %

Brighter Tomorrow with
Energy Saving




REDEEM PLUS


LED Bulb E27 A80S 2700 K

With an average efficiency of **133 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA80S272152NN



Light Projection Diagram



D: 80 mm H: 148 mm W: 80 mm




Color Spectrum Distribution

REDEEM PLUS


LED Bulb E27 A80S 3000 K

With an average efficiency of **140 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA80S302162NN



Light Projection Diagram



D: 80 mm H: 148 mm W: 80 mm



Color Spectrum Distribution

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA80S272152NN
GTIN (EAN13)	8684216000836
Case	A80
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A80S 2700K
Description	Tuled Redeem Plus LED Bulb E27 A80S 11.1W 1479lm 2700K Warm White



Physical Properties	
Width (W)	80 mm
Diameter (D)	80 mm
Height (H)	148 mm
Weight	48 g/unit
IP Class	IP50
Carton	50 (pcs)
Euro Pallet	18 (carton)
Euro Pallet	900 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	E (A-G)
Yearly Consumption	11.1 kWh/1000hours
AC Current	95 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.51

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	4.66 W
Beam Angle	190°
Luminous Flux	1,479 lm
CRI	85 Ra
Lighting Efficiency	133 lm/W
Color Temperature	2700 K
Color Temperature Name	Warm White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA80S302162NN
GTIN (EAN13)	8684216000508
Case	A80
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A80S 3000K
Description	Tuled Redeem Plus LED Bulb E27 A80S 11.1W 1553lm 3000K Mild White



Physical Properties	
Width (W)	80 mm
Diameter (D)	80 mm
Height (H)	148 mm
Weight	48 g/unit
IP Class	IP50
Carton	50 (pcs)
Euro Pallet	18 (carton)
Euro Pallet	900 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	11.1 kWh/1000hours
AC Current	94 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.51

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	4.80 W
Beam Angle	190°
Luminous Flux	1,553 lm
CRI	85 Ra
Lighting Efficiency	140 lm/W
Color Temperature	3000 K
Color Temperature Name	Mild White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

REDEEM PLUS


LED Bulb E27 A80S 3500 K

With an average efficiency of **141 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA80S352162NN



Light Projection Diagram



D: 80 mm H: 148 mm W: 80 mm




Color Spectrum Distribution

REDEEM PLUS


LED Bulb E27 A80S 4000 K

With an average efficiency of **145 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA80S402162NN



Light Projection Diagram



D: 80 mm H: 148 mm W: 80 mm



Color Spectrum Distribution

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA80S352162NN
GTIN (EAN13)	8684216000843
Case	A80
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A80S 3500K
Description	Tuled Redeem Plus LED Bulb E27 A80S 11.1W 1566lm 3500K Soft White



Physical Properties	
Width (W)	80 mm
Diameter (D)	80 mm
Height (H)	148 mm
Weight	48 g/unit
IP Class	IP50
Carton	50 (pcs)
Euro Pallet	18 (carton)
Euro Pallet	900 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	11.1 kWh/1000hours
AC Current	95 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.51

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	4.83 W
Beam Angle	190°
Luminous Flux	1,566 lm
CRI	85 Ra
Lighting Efficiency	141 lm/W
Color Temperature	3500 K
Color Temperature Name	Soft White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA80S402162NN
GTIN (EAN13)	8684216000522
Case	A80
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A80S 4000K
Description	Tuled Redeem Plus LED Bulb E27 A80S 11.1W 1607lm 4000K Natural White



Physical Properties	
Width (W)	80 mm
Diameter (D)	80 mm
Height (H)	148 mm
Weight	48 g/unit
IP Class	IP50
Carton	50 (pcs)
Euro Pallet	18 (carton)
Euro Pallet	900 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	11.1 kWh/1000hours
AC Current	95 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.51

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	4.97 W
Beam Angle	190°
Luminous Flux	1,607 lm
CRI	85 Ra
Lighting Efficiency	145 lm/W
Color Temperature	4000 K
Color Temperature Name	Natural White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

REDEEM PLUS


LED Bulb E27 A80S 5000 K

With an average efficiency of **145 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA80S502162NN



Light Projection Diagram



D: 80 mm H: 148 mm W: 80 mm




Color Spectrum Distribution

REDEEM PLUS


LED Bulb E27 A80S 5700 K

With an average efficiency of **145 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA80S572162NN



Light Projection Diagram



D: 80 mm H: 148 mm W: 80 mm



Color Spectrum Distribution

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA80S502162NN
GTIN (EAN13)	8684216000850
Case	A80
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A80S 5000K
Description	Tuled Redeem Plus LED Bulb E27 A80S 11.3W 1648lm 5000K Tuled White



Physical Properties	
Width (W)	80 mm
Diameter (D)	80 mm
Height (H)	148 mm
Weight	48 g/unit
IP Class	IP50
Carton	50 (pcs)
Euro Pallet	18 (carton)
Euro Pallet	900 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	11.3 kWh/1000hours
AC Current	97 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.51

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	5.26 W
Beam Angle	190°
Luminous Flux	1,648 lm
CRI	85 Ra
Lighting Efficiency	145 lm/W
Color Temperature	5000 K
Color Temperature Name	Tuled White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA80S572162NN
GTIN (EAN13)	8684216000867
Case	A80
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A80S 5700K
Description	Tuled Redeem Plus LED Bulb E27 A80S 11.3W 1637lm 5700K Gloss White



Physical Properties	
Width (W)	80 mm
Diameter (D)	80 mm
Height (H)	148 mm
Weight	48 g/unit
IP Class	IP50
Carton	50 (pcs)
Euro Pallet	18 (carton)
Euro Pallet	900 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	11.3 kWh/1000hours
AC Current	94 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.52

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	5.32 W
Beam Angle	190°
Luminous Flux	1,637 lm
CRI	85 Ra
Lighting Efficiency	145 lm/W
Color Temperature	5700 K
Color Temperature Name	Gloss White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

REDEEM PLUS


LED Bulb E27 A80S 6500 K

With an average efficiency of **145 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPA80S652162NN



Light Projection Diagram



D: 80 mm H: 148 mm W: 80 mm



Color Spectrum Distribution

General Info & ID

Product Type	LED Bulb
Series Name	Redeem Plus
Product Code	BLRPA80S652162NN
GTIN (EAN13)	8684216000874
Case	A80
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus LED Bulb E27 A80S 6500K
Description	Tuled Redeem Plus LED Bulb E27 A80S 11.1W 1613lm 6500K Cool White



Physical Properties

Width (W)	80 mm
Diameter (D)	80 mm
Height (H)	148 mm
Weight	48 g/unit
IP Class	IP50
Carton	50 (pcs)
Euro Pallet	18 (carton)
Euro Pallet	900 (pcs)

Light Characteristic

Declared Radiant Power	5.39 W
Beam Angle	190°
Luminous Flux	1,613 lm
CRI	85 Ra
Lighting Efficiency	145 lm/W
Color Temperature	6500 K
Color Temperature Name	Cool White

Thermal Character

Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	65°C
Safe to Touch	No

Electrical Characteristic

Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	11.1 kWh/1000hours
AC Current	93 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.52

Production Composition

Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime

Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions

Dimmable	No
----------	----


Environmental Features

RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Equivalent

Equivalent Incandescent Typical	125 W
Equivalent CFL	25 W
Equivalent LED Bulb	21 W
Tuled	11.1 W
Efficiency Compared to Inc.	1,017 %
Efficiency Compared to CFL	123 %
Eff. Compared to Traditional LED	77 %

In Every
Moment of Life



Redeem Plus Series Candle Bulbs

Take your lighting experience one step further and go beyond the ordinary with **Redeem Plus**. Experience the difference in energy efficiency and lighting quality with its innovative design and superior efficiency of **140 lm/W**. With **seven (7) different color options**, Redeem Plus offers lighting, comfort, and a new lifestyle.



High standard Quality manufacturing

With an average efficiency of **140 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to build a unique atmosphere in every space.



Product Code	GTIN EAN-13	Base	Case	Case Sub Type	Equivalent INC (W)	Equivalent CFL (W)	Equivalent LED (W)	Tuled Power (W)	Luminous Flux (lm)	Lighting Efficiency (lm/W)	Beam Angle (Degrees)	Color Temp. (K)	Color Temp. Name	Yearly Consumption (kWh/1000h)	Width (mm)	Diameter (mm)	Height (mm)	Weight (g/unit)	Carton (unit)	Euro Pallet (Carton)
BLRPC37S272601NN	8684216001475	E27	C37	S	45	9	8	4.3	571	134	185	2700	Warm White	4.3	37.00	37.00	100.00	18.03	100	60
BLRPC37S302601NN	8684216001482	E27	C37	S	45	9	8	4.3	590	136	185	3000	Mild White	4.3	37.00	37.00	100.00	18.03	100	60
BLRPC37S352601NN	8684216001499	E27	C37	S	45	9	8	4.3	606	141	185	3500	Soft White	4.3	37.00	37.00	100.00	18.03	100	60
BLRPC37S402601NN	8684216001505	E27	C37	S	45	9	8	4.3	609	142	185	4000	Natural White	4.3	37.00	37.00	100.00	18.03	100	60
BLRPC37S502601NN	8684216001512	E27	C37	S	50	10	8	4.3	621	145	185	5000	Tuled White	4.3	37.00	37.00	100.00	18.03	100	60
BLRPC37S572601NN	8684216001529	E27	C37	S	45	9	8	4.3	609	141	185	5700	Gloss White	4.3	37.00	37.00	100.00	18.03	100	60
BLRPC37S652601NN	8684216001536	E27	C37	S	45	9	8	4.3	594	138	185	6500	Cool White	4.3	37.00	37.00	100.00	18.03	100	60
BLRPC37A272601NN	8684216001543	E27	C37	A	45	9	8	4.3	570	132	205	2700	Warm White	4.3	37.00	37.00	124.00	19.12	100	48
BLRPC37A302601NN	8684216001550	E27	C37	A	45	9	8	4.3	581	135	205	3000	Mild White	4.3	37.00	37.00	124.00	19.12	100	48
BLRPC37A352601NN	8684216001567	E27	C37	A	45	9	8	4.2	590	140	205	3500	Soft White	4.2	37.00	37.00	124.00	19.12	100	48
BLRPC37A402601NN	8684216001574	E27	C37	A	45	9	8	4.3	604	141	205	4000	Natural White	4.3	37.00	37.00	124.00	19.12	100	48
BLRPC37A502601NN	8684216001581	E27	C37	A	45	9	8	4.3	610	143	205	5000	Tuled White	4.3	37.00	37.00	124.00	19.12	100	48
BLRPC37A572601NN	8684216001598	E27	C37	A	45	9	8	4.3	603	140	205	5700	Gloss White	4.3	37.00	37.00	124.00	19.12	100	48
BLRPC37A652601NN	8684216001604	E27	C37	A	45	9	8	4.2	579	137	205	6500	Cool White	4.2	37.00	37.00	124.00	19.12	100	48
BLRPC37S272601MN	8684216001604	E14	C37	S	45	9	8	4.3	571	134	185	2700	Warm White	4.3	37.00	37.00	100.00	15.78	100	60
BLRPC37S302601MN	8684216001765	E14	C37	S	45	9	8	4.3	590	136	185	3000	Mild White	4.3	37.00	37.00	100.00	15.78	100	60
BLRPC37S352601MN	8684216001772	E14	C37	S	45	9	8	4.3	606	141	185	3500	Soft White	4.3	37.00	37.00	100.00	15.78	100	60
BLRPC37S402601MN	8684216001789	E14	C37	S	45	9	8	4.3	609	142	185	4000	Natural White	4.3	37.00	37.00	100.00	15.78	100	60
BLRPC37S502601MN	8684216001796	E14	C37	S	50	10	8	4.3	621	145	185	5000	Tuled White	4.3	37.00	37.00	100.00	15.78	100	60
BLRPC37S572601MN	8684216001802	E14	C37	S	45	9	8	4.3	609	141	185	5700	Gloss White	4.3	37.00	37.00	100.00	15.78	100	60
BLRPC37S652601MN	8684216001819	E14	C37	S	45	9	8	4.3	594	138	185	6500	Cool White	4.3	37.00	37.00	100.00	15.78	100	60
BLRPC37A272601MN	8684216001826	E14	C37	A	45	9	8	4.3	570	132	205	2700	Warm White	4.3	37.00	37.00	124.00	17.07	100	48
BLRPC37A302601MN	8684216001833	E14	C37	A	45	9	8	4.3	581	135	205	3000	Mild White	4.3	37.00	37.00	124.00	17.07	100	48
BLRDC37A352501MN	8684216001840	E14	C37	A	45	9	8	4.2	590	140	205	3500	Soft White	4.2	37.00	37.00	124.00	17.07	100	48
BLRPC37A402601MN	8684216001857	E14	C37	A	45	9	8	4.3	604	141	205	4000	Natural White	4.3	37.00	37.00	124.00	17.07	100	48
BLRPC37A502601MN	8684216001864	E14	C37	A	45	9	8	4.3	610	143	205	5000	Tuled White	4.3	37.00	37.00	124.00	17.07	100	48
BLRPC37A572601MN	8684216001871	E14	C37	A	45	9	8	4.3	603	140	205	5700	Gloss White	4.3	37.00	37.00	124.00	17.07	100	48
BLRPC37A652601MN	8684216001888	E14	C37	A	45	9	8	4.2	579	137	205	6500	Cool White	4.2	37.00	37.00	124.00	17.07	100	48


The technical data was obtained under 25°C, 230V, and 50Hz test conditions. Technical data may vary depending on the conditions.

REDEEM PLUS


Candle Bulb E27 C37S 2700 K

With an average efficiency of **134 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37S272601NN



Light Projection Diagram



D: 37 mm H: 100 mm W: 37 mm




Color Spectrum Distribution

REDEEM PLUS


Candle Bulb E27 C37S 3000 K

With an average efficiency of **136 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37S302601NN



Light Projection Diagram



D: 37 mm H: 100 mm W: 37 mm



Color Spectrum Distribution

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37S272601NN
GTIN (EAN13)	8684216001475
Case	C37
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus Candle Bulb E27 C37S 2700K
Description	Tuled Redeem Plus Candle Bulb E27 C37S 4.3W 571lm 2700K Warm White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	100 mm
Weight	18 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	60 (carton)
Euro Pallet	6,000 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	E (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.78 W
Beam Angle	185°
Luminous Flux	571 lm
CRI	85 Ra
Lighting Efficiency	134 lm/W
Color Temperature	2700 K
Color Temperature Name	Warm White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37S302601NN
GTIN (EAN13)	8684216001482
Case	C37
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus Candle Bulb E27 C37S 3000K
Description	Tuled Redeem Plus Candle Bulb E27 C37S 4.3W 590lm 3000K Mild White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	100 mm
Weight	18 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	60 (carton)
Euro Pallet	6,000 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.82 W
Beam Angle	185°
Luminous Flux	590 lm
CRI	85 Ra
Lighting Efficiency	136 lm/W
Color Temperature	3000 K
Color Temperature Name	Mild White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

REDEEM PLUS


Candle Bulb E27 C37S 3500 K

With an average efficiency of **141 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37S352601NN



Light Projection Diagram



D: 37 mm H: 100 mm W: 37 mm




Color Spectrum Distribution

REDEEM PLUS


Candle Bulb E27 C37S 4000 K

With an average efficiency of **142 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37S402601NN



Light Projection Diagram



D: 37 mm H: 100 mm W: 37 mm



Color Spectrum Distribution

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37S352601NN
GTIN (EAN13)	8684216001499
Case	C37
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus Candle Bulb E27 C37S 3500K
Description	Tuled Redeem Plus Candle Bulb E27 C37S 4.3W 606lm 3500K Soft White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	100 mm
Weight	18 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	60 (carton)
Euro Pallet	6,000 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.84 W
Beam Angle	185°
Luminous Flux	606 lm
CRI	85 Ra
Lighting Efficiency	141 lm/W
Color Temperature	3500 K
Color Temperature Name	Soft White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37S402601NN
GTIN (EAN13)	8684216001505
Case	C37
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus Candle Bulb E27 C37S 4000K
Description	Tuled Redeem Plus Candle Bulb E27 C37S 4.3W 609lm 4000K Natural White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	100 mm
Weight	18 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	60 (carton)
Euro Pallet	6,000 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	47 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.87 W
Beam Angle	185°
Luminous Flux	609 lm
CRI	85 Ra
Lighting Efficiency	142 lm/W
Color Temperature	4000 K
Color Temperature Name	Natural White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

REDEEM PLUS


Candle Bulb E27 C37S 5000 K

With an average efficiency of **145 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37S502601NN



Light Projection Diagram



D: 37 mm H: 100 mm W: 37 mm




Color Spectrum Distribution

REDEEM PLUS


Candle Bulb E27 C37S 5700 K

With an average efficiency of **141 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37S572601NN



Light Projection Diagram



D: 37 mm H: 100 mm W: 37 mm



Color Spectrum Distribution

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37S502601NN
GTIN (EAN13)	8684216001512
Case	C37
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus Candle Bulb E27 C37S 5000K
Description	Tuled Redeem Plus Candle Bulb E27 C37S 4.3W 621lm 5000K Tuled White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	100 mm
Weight	18 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	60 (carton)
Euro Pallet	6,000 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.93 W
Beam Angle	185°
Luminous Flux	621 lm
CRI	85 Ra
Lighting Efficiency	145 lm/W
Color Temperature	5000 K
Color Temperature Name	Tuled White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Equivalent	
Equivalent Incandescent Typical	50 W
Equivalent CFL	10 W
Equivalent LED Bulb	8 W
Tuled	4.3 W
Efficiency Compared to Inc.	1,014 %
Efficiency Compared to CFL	123 %
Eff. Compared to Traditional LED	77 %

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37S572601NN
GTIN (EAN13)	8684216001529
Case	C37
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus Candle Bulb E27 C37S 5700K
Description	Tuled Redeem Plus Candle Bulb E27 C37S 4.3W 609lm 5700K Gloss White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	100 mm
Weight	18 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	60 (carton)
Euro Pallet	6,000 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.95 W
Beam Angle	185°
Luminous Flux	609 lm
CRI	85 Ra
Lighting Efficiency	141 lm/W
Color Temperature	5700 K
Color Temperature Name	Gloss White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No


Equivalent	
Equivalent Incandescent Typical	45 W
Equivalent CFL	9 W
Equivalent LED Bulb	8 W
Tuled	4.3 W
Efficiency Compared to Inc.	982 %
Efficiency Compared to CFL	116 %
Eff. Compared to Traditional LED	72 %

REDEEM PLUS


Candle Bulb E27 C37S 6500 K

With an average efficiency of **138 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37S652601NN



Light Projection Diagram



D: 37 mm H: 100 mm W: 37 mm



Color Spectrum Distribution

General Info & ID	
Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37S652601NN
GTIN (EAN13)	8684216001536
Case	C37
Case Sub Type	S
Base	E27
Description	Tuled Redeem Plus Candle Bulb E27 C37S 6500K
Description	Tuled Redeem Plus Candle Bulb E27 C37S 4.3W 594lm 6500K Cool White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	100 mm
Weight	18 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	60 (carton)
Euro Pallet	6,000 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.94 W
Beam Angle	185°
Luminous Flux	594 lm
CRI	85 Ra
Lighting Efficiency	138 lm/W
Color Temperature	6500 K
Color Temperature Name	Cool White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Equivalent	
Equivalent Incandescent Typical	45 W
Equivalent CFL	9 W
Equivalent LED Bulb	8 W
Tuled	4.3 W
Efficiency Compared to Inc.	963 %
Efficiency Compared to CFL	113 %
Eff. Compared to Traditional LED	68 %

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

Functions	
Dimmable	No

The technical data was obtained under 25°C, 230V, and 50Hz test conditions.
Technical data may vary depending on the conditions.




REDEEM PLUS


Candle Bulb E27 C37A 2700 K

With an average efficiency of **132 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37A272601NN



Light Projection Diagram



D: 37 mm H: 124 mm W: 37 mm




Color Spectrum Distribution

REDEEM PLUS


Candle Bulb E27 C37A 3000 K

With an average efficiency of **135 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37A302601NN



Light Projection Diagram



D: 37 mm H: 124 mm W: 37 mm



Color Spectrum Distribution

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37A272601NN
GTIN (EAN13)	8684216001543
Case	C37
Case Sub Type	A
Base	E27
Description	Tuled Redeem Plus Candle Bulb E27 C37A 2700K
Description	Tuled Redeem Plus Candle Bulb E27 C37A 4.3W 570lm 2700K Warm White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	124 mm
Weight	19 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	4,800 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	E (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.78 W
Beam Angle	205°
Luminous Flux	570 lm
CRI	85 Ra
Lighting Efficiency	132 lm/W
Color Temperature	2700 K
Color Temperature Name	Warm White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37A302601NN
GTIN (EAN13)	8684216001550
Case	C37
Case Sub Type	A
Base	E27
Description	Tuled Redeem Plus Candle Bulb E27 C37A 3000K
Description	Tuled Redeem Plus Candle Bulb E27 C37A 4.3W 581lm 3000K Mild White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	124 mm
Weight	19 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	4,800 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.79 W
Beam Angle	205°
Luminous Flux	581 lm
CRI	85 Ra
Lighting Efficiency	135 lm/W
Color Temperature	3000 K
Color Temperature Name	Mild White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

REDEEM PLUS


Candle Bulb E27 C37A 3500 K

With an average efficiency of **140 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37A352601NN



Light Projection Diagram



D: 37 mm H: 124 mm W: 37 mm




Color Spectrum Distribution

REDEEM PLUS


Candle Bulb E27 C37A 4000 K

With an average efficiency of **141 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37A402601NN



Light Projection Diagram



D: 37 mm H: 124 mm W: 37 mm



Color Spectrum Distribution

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37A352601NN
GTIN (EAN13)	8684216001567
Case	C37
Case Sub Type	A
Base	E27
Description	Tuled Redeem Plus Candle Bulb E27 C37A 3500K
Description	Tuled Redeem Plus Candle Bulb E27 C37A 4.2W 590lm 3500K Soft White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	124 mm
Weight	19 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	4,800 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.2 kWh/1000hours
AC Current	47 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.80 W
Beam Angle	205°
Luminous Flux	590 lm
CRI	85 Ra
Lighting Efficiency	140 lm/W
Color Temperature	3500 K
Color Temperature Name	Soft White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37A402601NN
GTIN (EAN13)	8684216001574
Case	C37
Case Sub Type	A
Base	E27
Description	Tuled Redeem Plus Candle Bulb E27 C37A 4000K
Description	Tuled Redeem Plus Candle Bulb E27 C37A 4.3W 604lm 4000K Natural White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	124 mm
Weight	19 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	4,800 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.87 W
Beam Angle	205°
Luminous Flux	604 lm
CRI	85 Ra
Lighting Efficiency	141 lm/W
Color Temperature	4000 K
Color Temperature Name	Natural White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

REDEEM PLUS


Candle Bulb E27 C37A 5000 K

With an average efficiency of **143 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37A502601NN



Light Projection Diagram



D: 37 mm H: 124 mm W: 37 mm




Color Spectrum Distribution

REDEEM PLUS


Candle Bulb E27 C37A 5700 K

With an average efficiency of **140 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37A572601NN



Light Projection Diagram



D: 37 mm H: 124 mm W: 37 mm



Color Spectrum Distribution

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37A502601NN
GTIN (EAN13)	8684216001581
Case	C37
Case Sub Type	A
Base	E27
Description	Tuled Redeem Plus Candle Bulb E27 C37A 5000K
Description	Tuled Redeem Plus Candle Bulb E27 C37A 4.3W 610lm 5000K Tuled White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	124 mm
Weight	19 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	4,800 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.91 W
Beam Angle	205°
Luminous Flux	610 lm
CRI	85 Ra
Lighting Efficiency	143 lm/W
Color Temperature	5000 K
Color Temperature Name	Tuled White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Equivalent	
Equivalent Incandescent Typical	45 W
Equivalent CFL	9 W
Equivalent LED Bulb	8 W
Tuled	4.3 W
Efficiency Compared to Inc.	996 %
Efficiency Compared to CFL	119 %
Eff. Compared to Traditional LED	74 %

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37A572601NN
GTIN (EAN13)	8684216001598
Case	C37
Case Sub Type	A
Base	E27
Description	Tuled Redeem Plus Candle Bulb E27 C37A 5700K
Description	Tuled Redeem Plus Candle Bulb E27 C37A 4.3W 603lm 5700K Gloss White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	124 mm
Weight	19 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	4,800 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.94 W
Beam Angle	205°
Luminous Flux	603 lm
CRI	85 Ra
Lighting Efficiency	140 lm/W
Color Temperature	5700 K
Color Temperature Name	Gloss White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

REDEEM PLUS


Candle Bulb E27 C37A 6500 K

With an average efficiency of **137 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37A652601NN



Light Projection Diagram



D: 37 mm H: 124 mm W: 37 mm



Color Spectrum Distribution

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37A652601NN
GTIN (EAN13)	8684216001604
Case	C37
Case Sub Type	A
Base	E27
Description	Tuled Redeem Plus Candle Bulb E27 C37A 6500K
Description	Tuled Redeem Plus Candle Bulb E27 C37A 4.2W 579lm 6500K Cool White



Physical Properties

Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	124 mm
Weight	19 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	4,800 (pcs)

Light Characteristic

Declared Radiant Power	1.90 W
Beam Angle	205°
Luminous Flux	579 lm
CRI	85 Ra
Lighting Efficiency	137 lm/W
Color Temperature	6500 K
Color Temperature Name	Cool White

Thermal Character

Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

Electrical Characteristic

Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.2 kWh/1000hours
AC Current	47 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Production Composition

Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime

Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions

Dimmable	No
----------	----

Environmental Features

RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Equivalent

Equivalent Incandescent Typical	45 W
Equivalent CFL	9 W
Equivalent LED Bulb	8 W
Tuled	4.2 W
Efficiency Compared to Inc.	957 %
Efficiency Compared to CFL	111 %
Eff. Compared to Traditional LED	68 %

The technical data was obtained under 25°C, 230V, and 50Hz test conditions.
Technical data may vary depending on the conditions.




ti

REDEEM PLUS


Candle Bulb E14 C37S 2700 K

With an average efficiency of **134 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37S272601MN



Light Projection Diagram



D: 37 mm H: 100 mm W: 37 mm




Color Spectrum Distribution

REDEEM PLUS


Candle Bulb E14 C37S 3000 K

With an average efficiency of **136 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37S302601MN



Light Projection Diagram



D: 37 mm H: 100 mm W: 37 mm



Color Spectrum Distribution

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37S272601MN
GTIN (EAN13)	8684216001758
Case	C37
Case Sub Type	S
Base	E14
Description	Tuled Redeem Plus Candle Bulb E14 C37S 2700K
Description	Tuled Redeem Plus Candle Bulb E14 C37S 4.3W 571lm 2700K Warm White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	100 mm
Weight	16 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	60 (carton)
Euro Pallet	6,000 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	E (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.78 W
Beam Angle	185°
Luminous Flux	571 lm
CRI	85 Ra
Lighting Efficiency	134 lm/W
Color Temperature	2700 K
Color Temperature Name	Warm White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37S302601MN
GTIN (EAN13)	8684216001765
Case	C37
Case Sub Type	S
Base	E14
Description	Tuled Redeem Plus Candle Bulb E14 C37S 3000K
Description	Tuled Redeem Plus Candle Bulb E14 C37S 4.3W 590lm 3000K Mild White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	100 mm
Weight	16 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	60 (carton)
Euro Pallet	6,000 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.82 W
Beam Angle	185°
Luminous Flux	590 lm
CRI	85 Ra
Lighting Efficiency	136 lm/W
Color Temperature	3000 K
Color Temperature Name	Mild White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

REDEEM PLUS


Candle Bulb E14 C37S 3500 K

With an average efficiency of **141 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37S352601MN



Light Projection Diagram



D: 37 mm H: 100 mm W: 37 mm




Color Spectrum Distribution

REDEEM PLUS


Candle Bulb E14 C37S 4000 K

With an average efficiency of **142 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37S402601MN



Light Projection Diagram



D: 37 mm H: 100 mm W: 37 mm



Color Spectrum Distribution

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37S352601MN
GTIN (EAN13)	8684216001772
Case	C37
Case Sub Type	S
Base	E14
Description	Tuled Redeem Plus Candle Bulb E14 C37S 3500K
Description	Tuled Redeem Plus Candle Bulb E14 C37S 4.3W 606lm 3500K Soft White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	100 mm
Weight	16 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	60 (carton)
Euro Pallet	6,000 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.84 W
Beam Angle	185°
Luminous Flux	606 lm
CRI	85 Ra
Lighting Efficiency	141 lm/W
Color Temperature	3500 K
Color Temperature Name	Soft White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37S402601MN
GTIN (EAN13)	8684216001789
Case	C37
Case Sub Type	S
Base	E14
Description	Tuled Redeem Plus Candle Bulb E14 C37S 4000K
Description	Tuled Redeem Plus Candle Bulb E14 C37S 4.3W 609lm 4000K Natural White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	100 mm
Weight	16 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	60 (carton)
Euro Pallet	6,000 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	47 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.87 W
Beam Angle	185°
Luminous Flux	609 lm
CRI	85 Ra
Lighting Efficiency	142 lm/W
Color Temperature	4000 K
Color Temperature Name	Natural White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

REDEEM PLUS


Candle Bulb E14 C37S 5000 K

With an average efficiency of **145 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37S502601MN



Light Projection Diagram



D: 37 mm H: 100 mm W: 37 mm




Color Spectrum Distribution

REDEEM PLUS


Candle Bulb E14 C37S 5700 K

With an average efficiency of **141 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37S572601MN



Light Projection Diagram



D: 37 mm H: 100 mm W: 37 mm



Color Spectrum Distribution

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37S502601MN
GTIN (EAN13)	8684216001796
Case	C37
Case Sub Type	S
Base	E14
Description	Tuled Redeem Plus Candle Bulb E14 C37S 5000K
Description	Tuled Redeem Plus Candle Bulb E14 C37S 4.3W 621lm 5000K Tuled White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	100 mm
Weight	16 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	60 (carton)
Euro Pallet	6,000 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.93 W
Beam Angle	185°
Luminous Flux	621 lm
CRI	85 Ra
Lighting Efficiency	145 lm/W
Color Temperature	5000 K
Color Temperature Name	Tuled White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Equivalent	
Equivalent Incandescent Typical	50 W
Equivalent CFL	10 W
Equivalent LED Bulb	8 W
Tuled	4.3 W
Efficiency Compared to Inc.	1,014 %
Efficiency Compared to CFL	123 %
Eff. Compared to Traditional LED	77 %

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37S572601MN
GTIN (EAN13)	8684216001802
Case	C37
Case Sub Type	S
Base	E14
Description	Tuled Redeem Plus Candle Bulb E14 C37S 5700K
Description	Tuled Redeem Plus Candle Bulb E14 C37S 4.3W 609lm 5700K Gloss White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	100 mm
Weight	16 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	60 (carton)
Euro Pallet	6,000 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.95 W
Beam Angle	185°
Luminous Flux	609 lm
CRI	85 Ra
Lighting Efficiency	141 lm/W
Color Temperature	5700 K
Color Temperature Name	Gloss White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No


Equivalent	
Equivalent Incandescent Typical	45 W
Equivalent CFL	9 W
Equivalent LED Bulb	8 W
Tuled	4.3 W
Efficiency Compared to Inc.	982 %
Efficiency Compared to CFL	116 %
Eff. Compared to Traditional LED	72 %

REDEEM PLUS


Candle Bulb E14 C37S 6500 K

With an average efficiency of **138 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37S652601MN



Light Projection Diagram



D: 37 mm H: 100 mm W: 37 mm



Color Spectrum Distribution

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37S652601MN
GTIN (EAN13)	8684216001819
Case	C37
Case Sub Type	S
Base	E14
Description	Tuled Redeem Plus Candle Bulb E14 C37S 6500K
Description	Tuled Redeem Plus Candle Bulb E14 C37S 4.3W 594lm 6500K Cool White



Physical Properties

Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	100 mm
Weight	16 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	60 (carton)
Euro Pallet	6,000 (pcs)

Light Characteristic

Declared Radiant Power	1.94 W
Beam Angle	185°
Luminous Flux	594 lm
CRI	85 Ra
Lighting Efficiency	138 lm/W
Color Temperature	6500 K
Color Temperature Name	Cool White

Thermal Character

Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

Electrical Characteristic

Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Production Composition

Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime

Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions

Dimmable	No
----------	----

Environmental Features

RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Equivalent

Equivalent Incandescent Typical	45 W
Equivalent CFL	9 W
Equivalent LED Bulb	8 W
Tuled	4.3 W
Efficiency Compared to Inc.	963 %
Efficiency Compared to CFL	113 %
Eff. Compared to Traditional LED	68 %

The technical data was obtained under 25°C, 230V, and 50Hz test conditions.
Technical data may vary depending on the conditions.




REDEEM PLUS


Candle Bulb E14 C37A 2700 K

With an average efficiency of **132 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37A272601MN



Light Projection Diagram



D: 37 mm H: 124 mm W: 37 mm




Color Spectrum Distribution

REDEEM PLUS


Candle Bulb E14 C37A 3000 K

With an average efficiency of **135 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37A302601MN



Light Projection Diagram



D: 37 mm H: 124 mm W: 37 mm



Color Spectrum Distribution

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37A272601MN
GTIN (EAN13)	8684216001826
Case	C37
Case Sub Type	A
Base	E14
Description	Tuled Redeem Plus Candle Bulb E14 C37A 2700K
Description	Tuled Redeem Plus Candle Bulb E14 C37A 4.3W 570lm 2700K Warm White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	124 mm
Weight	17 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	4,800 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	E (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.78 W
Beam Angle	205°
Luminous Flux	570 lm
CRI	85 Ra
Lighting Efficiency	132 lm/W
Color Temperature	2700 K
Color Temperature Name	Warm White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Equivalent	
Equivalent Incandescent Typical	45 W
Equivalent CFL	9 W
Equivalent LED Bulb	8 W
Tuled	4.3 W
Efficiency Compared to Inc.	917 %
Efficiency Compared to CFL	103 %
Eff. Compared to Traditional LED	61 %

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37A302601MN
GTIN (EAN13)	8684216001833
Case	C37
Case Sub Type	A
Base	E14
Description	Tuled Redeem Plus Candle Bulb E14 C37A 3000K
Description	Tuled Redeem Plus Candle Bulb E14 C37A 4.3W 581lm 3000K Mild White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	124 mm
Weight	17 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	4,800 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.79 W
Beam Angle	205°
Luminous Flux	581 lm
CRI	85 Ra
Lighting Efficiency	135 lm/W
Color Temperature	3000 K
Color Temperature Name	Mild White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

REDEEM PLUS


Candle Bulb E14 C37A 3500 K

With an average efficiency of **140 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37A352601MN



Light Projection Diagram



D: 37 mm H: 124 mm W: 37 mm




Color Spectrum Distribution

REDEEM PLUS


Candle Bulb E14 C37A 4000 K

With an average efficiency of **141 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37A402601MN



Light Projection Diagram



D: 37 mm H: 124 mm W: 37 mm



Color Spectrum Distribution

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37A352601MN
GTIN (EAN13)	8684216001840
Case	C37
Case Sub Type	A
Base	E14
Description	Tuled Redeem Plus Candle Bulb E14 C37A 3500K
Description	Tuled Redeem Plus Candle Bulb E14 C37A 4.2W 590lm 3500K Soft White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	124 mm
Weight	17 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	4,800 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.2 kWh/1000hours
AC Current	47 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.80 W
Beam Angle	205°
Luminous Flux	590 lm
CRI	85 Ra
Lighting Efficiency	140 lm/W
Color Temperature	3500 K
Color Temperature Name	Soft White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Equivalent	
Equivalent Incandescent Typical	45 W
Equivalent CFL	9 W
Equivalent LED Bulb	8 W
Tuled	4.2 W
Efficiency Compared to Inc.	979 %
Efficiency Compared to CFL	116 %
Eff. Compared to Traditional LED	71 %

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37A402601MN
GTIN (EAN13)	8684216001857
Case	C37
Case Sub Type	A
Base	E14
Description	Tuled Redeem Plus Candle Bulb E14 C37A 4000K
Description	Tuled Redeem Plus Candle Bulb E14 C37A 4.3W 604lm 4000K Natural White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	124 mm
Weight	17 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	4,800 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.87 W
Beam Angle	205°
Luminous Flux	604 lm
CRI	85 Ra
Lighting Efficiency	141 lm/W
Color Temperature	4000 K
Color Temperature Name	Natural White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

REDEEM PLUS


Candle Bulb E14 C37A 5000 K

With an average efficiency of **143 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37A502601MN



Light Projection Diagram



D: 37 mm H: 124 mm W: 37 mm




Color Spectrum Distribution

REDEEM PLUS


Candle Bulb E14 C37A 5700 K

With an average efficiency of **140 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37A572601MN



Light Projection Diagram



D: 37 mm H: 124 mm W: 37 mm



Color Spectrum Distribution

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37A502601MN
GTIN (EAN13)	8684216001864
Case	C37
Case Sub Type	A
Base	E14
Description	Tuled Redeem Plus Candle Bulb E14 C37A 5000K
Description	Tuled Redeem Plus Candle Bulb E14 C37A 4.3W 610lm 5000K Tuled White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	124 mm
Weight	17 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	4,800 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.91 W
Beam Angle	205°
Luminous Flux	610 lm
CRI	85 Ra
Lighting Efficiency	143 lm/W
Color Temperature	5000 K
Color Temperature Name	Tuled White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Equivalent	
Equivalent Incandescent Typical	45 W
Equivalent CFL	9 W
Equivalent LED Bulb	8 W
Tuled	4.3 W
Efficiency Compared to Inc.	996 %
Efficiency Compared to CFL	119 %
Eff. Compared to Traditional LED	74 %

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Candle Bulb
Series Name	Redeem Plus
Product Code	BLRPC37A572601MN
GTIN (EAN13)	8684216001871
Case	C37
Case Sub Type	A
Base	E14
Description	Tuled Redeem Plus Candle Bulb E14 C37A 5700K
Description	Tuled Redeem Plus Candle Bulb E14 C37A 4.3W 603lm 5700K Gloss White



Physical Properties	
Width (W)	37 mm
Diameter (D)	37 mm
Height (H)	124 mm
Weight	17 g/unit
IP Class	IP50
Carton	100 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	4,800 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	4.3 kWh/1000hours
AC Current	48 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.39

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	1.94 W
Beam Angle	205°
Luminous Flux	603 lm
CRI	85 Ra
Lighting Efficiency	140 lm/W
Color Temperature	5700 K
Color Temperature Name	Gloss White

Production Composition	
Driver Type	On Board IC
Body Material	PBT
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

REDEEM PLUS


Candle Bulb E14 C37A 6500 K

With an average efficiency of **137 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


BLRPC37A652601MN



Light Projection Diagram



D: 37 mm H: 124 mm W: 37 mm



Color Spectrum Distribution

General Info & ID			
Product Type		Candle Bulb	
Series Name		Redeem Plus	
Product Code		BLRPC37A652601MN	
GTIN (EAN13)		8684216001888	
Case		C37	
Case Sub Type		A	
Base		E14	
Description		Tuled Redeem Plus Candle Bulb E14 C37A 6500K	
Description		Tuled Redeem Plus Candle Bulb E14 C37A 4.2W 579lm 6500K Cool White	
			
Physical Properties		Electrical Characteristic	
Width (W)	37 mm	Efficiency Class (EU 2019/2015)	D (A-G)
Diameter (D)	37 mm	Yearly Consumption	4.2 kWh/1000hours
Height (H)	124 mm	AC Current	47 mA
Weight	17 g/unit	Mains Voltage Rate Minimum	110 VAC
IP Class	IP50	Mains Voltage Rate Maximum	240 VAC
Carton	100 (pcs)	Mains Frequency Minimum	40 Hz
Euro Pallet	48 (carton)	Mains Frequency Maximum	60 Hz
Euro Pallet	4,800 (pcs)	Power Factor	0.39
Light Characteristic		Environmental Features	
Declared Radiant Power	1.90 W	RoHs 2011/65/EU Compliant	Yes
Beam Angle	205°	Hg Free Compliant	Yes
Luminous Flux	579 lm	EAC	Yes
CRI	85 Ra	CE	Yes
Lighting Efficiency	137 lm/W	Recyclable	No
Color Temperature	6500 K	Fragile	Yes
Color Temperature Name	Cool White	Protected Against Water	No
		Safe to Trash	No
Thermal Character		Production Composition	
Operating Temperature Min	-20°C	Driver Type	On Board IC
Operating Temperature Max	50°C	Body Material	PBT
Surface Temperature	60°C	LED Chip Vendor	Samsung / Cree
Safe to Touch	No	Diffuser Material	PC - Polycarbonates
Functions		Equivalent	
Dimmable	No	Equivalent Incandescent Typical	45 W
		Equivalent CFL	9 W
		Equivalent LED Bulb	8 W
		Tuled	4.2 W
		Efficiency Compared to Inc.	957 %
		Efficiency Compared to CFL	111 %
		Eff. Compared to Traditional LED	68 %

The technical data was obtained under 25°C, 230V, and 50Hz test conditions.
Technical data may vary depending on the conditions.





Redeem Plus Series Downlight

Take your lighting experience one step further and go beyond the ordinary with **Redeem Plus**. Experience the difference in energy efficiency and lighting quality with its innovative design and superior efficiency of **140 lm/W**. With **seven (7) different color options**, Redeem Plus offers lighting, comfort, and a new lifestyle.



High standard Quality manufacturing

With an average efficiency of **140 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to build a unique atmosphere in every space.



Product Code	GTIN EAN-13	Base	Case	Case Sub Type	Equivalent INC (W)	Equivalent CFL (W)	Equivalent LED (W)	Tuled Power (W)	Luminous Flux (lm)	Lighting Efficiency (lm/W)	Beam Angle (Degrees)	Color Temp. (K)	Color Temp. Name	Yearly Consumption (kWh/1000h)	Width (mm)	Diameter (mm)	Height (mm)	Weight (g/unit)	Carton (unit)	Euro Pallet (Carton)
DLRPC10W272651NN	8684216001093	N/A	C10	W	50	10	9	5.0	650	130	94	2700	Warm White	5.0	100.50	100.50	27.50	79.70	64	48
DLRPC10W302651NN	8684216001109	N/A	C10	W	50	10	9	5.0	657	131	94	3000	Mild White	5.0	100.50	100.50	27.50	79.70	64	48
DLRPC10W352701NN	8684216001116	N/A	C10	W	50	10	9	5.0	678	136	94	3500	Soft White	5.0	100.50	100.50	27.50	79.70	64	48
DLRPC10W402701NN	8684216001123	N/A	C10	W	50	10	9	5.0	681	137	94	4000	Natural White	5.0	100.50	100.50	27.50	79.70	64	48
DLRPC10W502701NN	8684216001130	N/A	C10	W	55	11	9	5.0	693	139	94	5000	Tuled White	5.0	100.50	100.50	27.50	79.70	64	48
DLRPC10W572701NN	8684216001147	N/A	C10	W	50	10	9	5.0	675	136	94	5700	Gloss White	5.0	100.50	100.50	27.50	79.70	64	48
DLRPC10W652701NN	8684216001154	N/A	C10	W	50	10	9	5.0	672	135	94	6500	Cool White	5.0	100.50	100.50	27.50	79.70	64	48
DLRPC12W272851NN	8684216001161	N/A	C12	W	65	13	11	6.2	835	135	95	2700	Warm White	6.2	118.50	118.50	27.50	104.70	60	27
DLRPC12W302901NN	8684216001178	N/A	C12	W	65	13	11	6.3	864	137	95	3000	Mild White	6.3	118.50	118.50	27.50	104.70	60	27
DLRPC12W352901NN	8684216001185	N/A	C12	W	70	14	12	6.2	888	143	95	3500	Soft White	6.2	118.50	118.50	27.50	104.70	60	27
DLRPC12W402901NN	8684216001192	N/A	C12	W	70	14	12	6.2	889	143	95	4000	Natural White	6.2	118.50	118.50	27.50	10.70	60	27
DLRPC12W502901NN	8684216001208	N/A	C12	W	70	14	12	6.2	902	145	95	5000	Cool White	6.2	118.50	118.50	27.50	104.70	60	27
DLRPC12W572901NN	8684216001215	N/A	C12	W	70	14	12	6.2	885	142	95	5700	Gloss White	6.2	118.50	118.50	27.50	104.70	60	27
DLRPC12W652901NN	8684216001222	N/A	C12	W	65	13	11	6.2	872	140	95	6500	Cool White	6.2	118.50	118.50	27.50	104.70	60	27
DLRPC18W272172NN	8684216001239	N/A	C18	W	130	26	22	12.1	1.720	143	98	2700	Warm White	12.1	180.00	180.00	27.50	209.60	20	36
DLRPC18W302182NN	8684216001246	N/A	C18	W	135	27	23	12.2	1.767	145	98	3000	Mild White	12.2	180.00	180.00	27.50	209.60	20	36
DLRPC18W352182NN	8684216001253	N/A	C18	W	140	28	23	12.1	1.811	149	98	3500	Soft White	12.1	180.00	180.00	27.50	209.60	20	36
DLRPC18W402182NN	8684216001260	N/A	C18	W	140	28	23	12.2	1.831	151	98	4000	Natural White	12.2	180.00	180.00	27.50	209.60	20	36
DLRPC18W502182NN	8684216001277	N/A	C18	W	145	29	24	12.2	1.858	153	98	5000	Tuled White	12.2	180.00	180.00	27.50	209.60	20	36
DLRPC18W572182NN	8684216001284	N/A	C18	W	140	28	23	12.2	1.819	149	98	5700	Gloss White	12.2	180.00	180.00	27.50	209.60	20	36
DLRPC18W652182NN	8684216001291	N/A	C18	W	140	28	23	12.2	1.799	148	98	6500	Cool White	12.2	180.00	180.00	27.50	209.60	20	36


The technical data was obtained under 25°C, 230V, and 50Hz test conditions. Technical data may vary depending on the conditions.

REDEEM PLUS


Downlight C10W 2700 K

With an average efficiency of **130 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC10W272651NN




Light Projection Diagram



D: 100.5 mm H: 27.5 mm W: 100.5 mm



Min. 75 mm
Maks. 95 mm
2.95 inch 3.74 inch




Color Spectrum Distribution

REDEEM PLUS


Downlight C10W 3000 K

With an average efficiency of **131 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC10W302651NN




Light Projection Diagram



D: 100.5 mm H: 27.5 mm W: 100.5 mm



Min. 75 mm
Maks. 95 mm
2.95 inch 3.74 inch



Color Spectrum Distribution

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC10W272651NN
GTIN (EAN13)	8684216001093
Case	C10
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C10W 2700K
Description	Tuled Redeem Plus Downlight C10W 5.0W 650lm 2700K Warm White



Physical Properties	
Width (W)	100.5 mm
Diameter (D)	100.5 mm
Height (H)	27.5 mm
Weight	80 g/unit
IP Class	IP50
Carton	64 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	3,072 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	E (A-G)
Yearly Consumption	5.0 kWh/1000hours
AC Current	51 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.43

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	2.00 W
Beam Angle	94°
Luminous Flux	650 lm
CRI	85 Ra
Lighting Efficiency	130 lm/W
Color Temperature	2700 K
Color Temperature Name	Warm White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC10W302651NN
GTIN (EAN13)	8684216001109
Case	C10
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C10W 3000K
Description	Tuled Redeem Plus Downlight C10W 5.0W 657lm 3000K Mild White



Physical Properties	
Width (W)	100.5 mm
Diameter (D)	100.5 mm
Height (H)	27.5 mm
Weight	80 g/unit
IP Class	IP50
Carton	64 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	3,072 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	E (A-G)
Yearly Consumption	5.0 kWh/1000hours
AC Current	51 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.43

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	2.00 W
Beam Angle	94°
Luminous Flux	657 lm
CRI	85 Ra
Lighting Efficiency	131 lm/W
Color Temperature	3000 K
Color Temperature Name	Mild White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

REDEEM PLUS


Downlight C10W 3500 K

With an average efficiency of **136 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC10W352701NN




Light Projection Diagram



D: 100.5 mm H: 27.5 mm W: 100.5 mm



Min. 75 mm
Maks. 95 mm
2.95 inch 3.74 inch




Color Spectrum Distribution

REDEEM PLUS


Downlight C10W 4000 K

With an average efficiency of **137 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC10W402701NN




Light Projection Diagram



D: 100.5 mm H: 27.5 mm W: 100.5 mm



Min. 75 mm
Maks. 95 mm
2.95 inch 3.74 inch



Color Spectrum Distribution

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC10W352701NN
GTIN (EAN13)	8684216001116
Case	C10
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C10W 3500K
Description	Tuled Redeem Plus Downlight C10W 5.0W 678lm 3500K Soft White



Physical Properties	
Width (W)	100.5 mm
Diameter (D)	100.5 mm
Height (H)	27.5 mm
Weight	80 g/unit
IP Class	IP50
Carton	64 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	3,072 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	5.0 kWh/1000hours
AC Current	51 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.43

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	2.02 W
Beam Angle	94°
Luminous Flux	678 lm
CRI	85 Ra
Lighting Efficiency	136 lm/W
Color Temperature	3500 K
Color Temperature Name	Soft White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC10W402701NN
GTIN (EAN13)	8684216001123
Case	C10
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C10W 4000K
Description	Tuled Redeem Plus Downlight C10W 5.0W 681lm 4000K Natural White



Physical Properties	
Width (W)	100.5 mm
Diameter (D)	100.5 mm
Height (H)	27.5 mm
Weight	80 g/unit
IP Class	IP50
Carton	64 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	3,072 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	5.0 kWh/1000hours
AC Current	51 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.42

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	2.07 W
Beam Angle	94°
Luminous Flux	681 lm
CRI	85 Ra
Lighting Efficiency	137 lm/W
Color Temperature	4000 K
Color Temperature Name	Natural White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

REDEEM PLUS


Downlight C10W 5000 K

With an average efficiency of **139 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC10W502701NN




Light Projection Diagram



D: 100.5 mm H: 27.5 mm W: 100.5 mm



Min. 75 mm
Maks. 95 mm
2.95 inch 3.74 inch




Color Spectrum Distribution

REDEEM PLUS


Downlight C10W 5700 K

With an average efficiency of **136 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC10W572701NN




Light Projection Diagram



D: 100.5 mm H: 27.5 mm W: 100.5 mm



Min. 75 mm
Maks. 95 mm
2.95 inch 3.74 inch



Color Spectrum Distribution

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC10W502701NN
GTIN (EAN13)	8684216001130
Case	C10
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C10W 5000K
Description	Tuled Redeem Plus Downlight C10W 5.0W 693lm 5000K Tuled White



Physical Properties	
Width (W)	100.5 mm
Diameter (D)	100.5 mm
Height (H)	27.5 mm
Weight	80 g/unit
IP Class	IP50
Carton	64 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	3,072 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	5.0 kWh/1000hours
AC Current	51 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.43

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	2.12 W
Beam Angle	94°
Luminous Flux	693 lm
CRI	85 Ra
Lighting Efficiency	139 lm/W
Color Temperature	5000 K
Color Temperature Name	Tuled White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC10W572701NN
GTIN (EAN13)	8684216001147
Case	C10
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C10W 5700K
Description	Tuled Redeem Plus Downlight C10W 5.0W 675lm 5700K Gloss White



Physical Properties	
Width (W)	100.5 mm
Diameter (D)	100.5 mm
Height (H)	27.5 mm
Weight	80 g/unit
IP Class	IP50
Carton	64 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	3,072 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	5.0 kWh/1000hours
AC Current	51 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.42

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	2.12 W
Beam Angle	94°
Luminous Flux	675 lm
CRI	85 Ra
Lighting Efficiency	136 lm/W
Color Temperature	5700 K
Color Temperature Name	Gloss White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

REDEEM PLUS


Downlight C10W 6500 K

With an average efficiency of **135 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC10W652701NN




Light Projection Diagram



D: 100.5 mm H: 27.5 mm W: 100.5 mm



Min. 75 mm
Maks. 95 mm



Color Spectrum Distribution

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC10W652701NN
GTIN (EAN13)	8684216001154
Case	C10
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C10W 6500K
Description	Tuled Redeem Plus Downlight C10W 5.0W 672lm 6500K Cool White



Physical Properties

Width (W)	100.5 mm
Diameter (D)	100.5 mm
Height (H)	27.5 mm
Weight	80 g/unit
IP Class	IP50
Carton	64 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	3,072 (pcs)

Light Characteristic

Declared Radiant Power	2.15 W
Beam Angle	94°
Luminous Flux	672 lm
CRI	85 Ra
Lighting Efficiency	135 lm/W
Color Temperature	6500 K
Color Temperature Name	Cool White

Thermal Characer

Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

Electrical Characteristic

Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	5.0 kWh/1000hours
AC Current	51 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.43

Production Composition

Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime

Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions

Dimmable	No
----------	----

Environmental Features

RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Equivalent

Equivalent Incandescent Typical	50 W
Equivalent CFL	10 W
Equivalent LED Bulb	9 W
Tuled	5.0 W
Efficiency Compared to Inc.	939 %
Efficiency Compared to CFL	108 %
Eff. Compared to Traditional LED	65 %


The technical data was obtained under 25°C, 230V, and 50Hz test conditions.
Technical data may vary depending on the conditions.

REDEEM PLUS


Downlight C12W 2700 K

With an average efficiency of **135 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC12W272851NN




Light Projection Diagram



D: 118.5 mm H: 27.5 mm W: 118.5 mm



Min. 95 mm
Maks. 115 mm
3.74 inch 4.53 inch




Color Spectrum Distribution

REDEEM PLUS


Downlight C12W 3000 K

With an average efficiency of **137 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC12W302901NN




Light Projection Diagram



D: 118.5 mm H: 27.5 mm W: 118.5 mm



Min. 95 mm
Maks. 115 mm
3.74 inch 4.53 inch



Color Spectrum Distribution

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC12W272851NN
GTIN (EAN13)	8684216001161
Case	C12
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C12W 2700K
Description	Tuled Redeem Plus Downlight C12W 6.2W 835lm 2700K Warm White



Physical Properties	
Width (W)	118.5 mm
Diameter (D)	118.5 mm
Height (H)	27.5 mm
Weight	105 g/unit
IP Class	IP50
Carton	60 (pcs)
Euro Pallet	27 (carton)
Euro Pallet	1,620 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	E (A-G)
Yearly Consumption	6.2 kWh/1000hours
AC Current	60 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.45

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	2.57 W
Beam Angle	95°
Luminous Flux	835 lm
CRI	85 Ra
Lighting Efficiency	135 lm/W
Color Temperature	2700 K
Color Temperature Name	Warm White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC12W302901NN
GTIN (EAN13)	8684216001178
Case	C12
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C12W 3000K
Description	Tuled Redeem Plus Downlight C12W 6.3W 864lm 3000K Mild White



Physical Properties	
Width (W)	118.5 mm
Diameter (D)	118.5 mm
Height (H)	27.5 mm
Weight	105 g/unit
IP Class	IP50
Carton	60 (pcs)
Euro Pallet	27 (carton)
Euro Pallet	1,620 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	6.3 kWh/1000hours
AC Current	61 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.45

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	2.64 W
Beam Angle	95°
Luminous Flux	864 lm
CRI	85 Ra
Lighting Efficiency	137 lm/W
Color Temperature	3000 K
Color Temperature Name	Mild White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

REDEEM PLUS


Downlight C12W 3500 K

With an average efficiency of **143 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC12W352901NN




Light Projection Diagram



D: 118.5 mm H: 27.5 mm W: 118.5 mm



Min. 95 mm
Maks. 115 mm
3.74 inch 4.53 inch




Color Spectrum Distribution

REDEEM PLUS


Downlight C12W 4000 K

With an average efficiency of **143 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC12W402901NN




Light Projection Diagram



D: 118.5 mm H: 27.5 mm W: 118.5 mm



Min. 95 mm
Maks. 115 mm
3.74 inch 4.53 inch



Color Spectrum Distribution

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC12W352901NN
GTIN (EAN13)	8684216001185
Case	C12
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C12W 3500K
Description	Tuled Redeem Plus Downlight C12W 6.2W 888lm 3500K Soft White



Physical Properties	
Width (W)	118.5 mm
Diameter (D)	118.5 mm
Height (H)	27.5 mm
Weight	105 g/unit
IP Class	IP50
Carton	60 (pcs)
Euro Pallet	27 (carton)
Euro Pallet	1,620 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	6.2 kWh/1000hours
AC Current	60 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.45

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	2.66 W
Beam Angle	95°
Luminous Flux	888 lm
CRI	85 Ra
Lighting Efficiency	143 lm/W
Color Temperature	3500 K
Color Temperature Name	Soft White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC12W402901NN
GTIN (EAN13)	8684216001192
Case	C12
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C12W 4000K
Description	Tuled Redeem Plus Downlight C12W 6.2W 889lm 4000K Natural White



Physical Properties	
Width (W)	118.5 mm
Diameter (D)	118.5 mm
Height (H)	27.5 mm
Weight	105 g/unit
IP Class	IP50
Carton	60 (pcs)
Euro Pallet	27 (carton)
Euro Pallet	1,620 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	6.2 kWh/1000hours
AC Current	60 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.45

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	2.70 W
Beam Angle	95°
Luminous Flux	889 lm
CRI	85 Ra
Lighting Efficiency	143 lm/W
Color Temperature	4000 K
Color Temperature Name	Natural White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

REDEEM PLUS


Downlight C12W 5000 K

With an average efficiency of **145 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC12W502901NN




Light Projection Diagram



D: 118.5 mm H: 27.5 mm W: 118.5 mm



Min. 95 mm
Maks. 115 mm
3.74 inch 4.53 inch




Color Spectrum Distribution

REDEEM PLUS


Downlight C12W 5700 K

With an average efficiency of **142 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC12W572901NN




Light Projection Diagram



D: 118.5 mm H: 27.5 mm W: 118.5 mm



Min. 95 mm
Maks. 115 mm
3.74 inch 4.53 inch



Color Spectrum Distribution

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC12W502901NN
GTIN (EAN13)	8684216001208
Case	C12
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C12W 5000K
Description	Tuled Redeem Plus Downlight C12W 6.2W 902lm 5000K Tuled White



Physical Properties	
Width (W)	118.5 mm
Diameter (D)	118.5 mm
Height (H)	27.5 mm
Weight	105 g/unit
IP Class	IP50
Carton	60 (pcs)
Euro Pallet	27 (carton)
Euro Pallet	1,620 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	6.2 kWh/1000hours
AC Current	60 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.45

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	2.76 W
Beam Angle	95°
Luminous Flux	902 lm
CRI	85 Ra
Lighting Efficiency	145 lm/W
Color Temperature	5000 K
Color Temperature Name	Tuled White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC12W572901NN
GTIN (EAN13)	8684216001215
Case	C12
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C12W 5700K
Description	Tuled Redeem Plus Downlight C12W 6.2W 885lm 5700K Gloss White



Physical Properties	
Width (W)	118.5 mm
Diameter (D)	118.5 mm
Height (H)	27.5 mm
Weight	105 g/unit
IP Class	IP50
Carton	60 (pcs)
Euro Pallet	27 (carton)
Euro Pallet	1,620 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	6.2 kWh/1000hours
AC Current	60 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.45

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	2.78 W
Beam Angle	95°
Luminous Flux	885 lm
CRI	85 Ra
Lighting Efficiency	142 lm/W
Color Temperature	5700 K
Color Temperature Name	Gloss White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No

REDEEM PLUS


Downlight C12W 6500 K

With an average efficiency of **140 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC12W652901NN




Light Projection Diagram



D: 118.5 mm H: 27.5 mm W: 118.5 mm



Min. 95 mm
Maks. 115 mm
3.74 inch 4.53 inch



Color Spectrum Distribution

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC12W652901NN
GTIN (EAN13)	8684216001222
Case	C12
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C12W 6500K
Description	Tuled Redeem Plus Downlight C12W 6.2W 872lm 6500K Cool White



Physical Properties	
Width (W)	118.5 mm
Diameter (D)	118.5 mm
Height (H)	27.5 mm
Weight	105 g/unit
IP Class	IP50
Carton	60 (pcs)
Euro Pallet	27 (carton)
Euro Pallet	1,620 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	6.2 kWh/1000hours
AC Current	60 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.45

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	2.80 W
Beam Angle	95°
Luminous Flux	872 lm
CRI	85 Ra
Lighting Efficiency	140 lm/W
Color Temperature	6500 K
Color Temperature Name	Cool White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	60°C
Safe to Touch	No


The technical data was obtained under 25°C, 230V, and 50Hz test conditions. Technical data may vary depending on the conditions.

REDEEM PLUS



Downlight C18W 2700 K

With an average efficiency of **143 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC18W272172NN



Light Projection Diagram



Min. 148 mm
Maks. 176 mm
5.83 inch 6.93 inch




Color Spectrum Distribution

REDEEM PLUS



Downlight C18W 3000 K

With an average efficiency of **145 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC18W302182NN



Light Projection Diagram



Min. 148 mm
Maks. 176 mm
5.83 inch 6.93 inch



Color Spectrum Distribution

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC18W272172NN
GTIN (EAN13)	8684216001239
Case	C18
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C18W 2700K
Description	Tuled Redeem Plus Downlight C18W 12.1W 1720lm 2700K Warm White



Physical Properties	
Width (W)	180 mm
Diameter (D)	180 mm
Height (H)	27.5 mm
Weight	210 g/unit
IP Class	IP50
Carton	20 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	960 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	12.1 kWh/1000hours
AC Current	98 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.54

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	5.31 W
Beam Angle	98°
Luminous Flux	1,720 lm
CRI	85 Ra
Lighting Efficiency	143 lm/W
Color Temperature	2700 K
Color Temperature Name	Warm White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	50°C
Safe to Touch	No

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC18W302182NN
GTIN (EAN13)	8684216001246
Case	C18
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C18W 3000K
Description	Tuled Redeem Plus Downlight C18W 12.2W 1767lm 3000K Mild White



Physical Properties	
Width (W)	180 mm
Diameter (D)	180 mm
Height (H)	27.5 mm
Weight	210 g/unit
IP Class	IP50
Carton	20 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	960 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	12.2 kWh/1000hours
AC Current	99 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.54

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	5.38 W
Beam Angle	98°
Luminous Flux	1,767 lm
CRI	85 Ra
Lighting Efficiency	145 lm/W
Color Temperature	3000 K
Color Temperature Name	Mild White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	50°C
Safe to Touch	No

REDEEM PLUS




Downlight C18W 3500 K

With an average efficiency of **149 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.

DLRPC18W352182NN



Light Projection Diagram




Color Spectrum Distribution

REDEEM PLUS




Downlight C18W 4000 K

With an average efficiency of **151 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.

DLRPC18W402182NN



Light Projection Diagram



Color Spectrum Distribution

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC18W352182NN
GTIN (EAN13)	8684216001253
Case	C18
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C18W 3500K
Description	Tuled Redeem Plus Downlight C18W 12.1W 1811lm 3500K Soft White



Physical Properties	
Width (W)	180 mm
Diameter (D)	180 mm
Height (H)	27.5 mm
Weight	210 g/unit
IP Class	IP50
Carton	20 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	960 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	12.1 kWh/1000hours
AC Current	98 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.54

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	5.43 W
Beam Angle	98°
Luminous Flux	1,811 lm
CRI	85 Ra
Lighting Efficiency	149 lm/W
Color Temperature	3500 K
Color Temperature Name	Soft White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	50°C
Safe to Touch	No

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC18W402182NN
GTIN (EAN13)	8684216001260
Case	C18
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C18W 4000K
Description	Tuled Redeem Plus Downlight C18W 12.2W 1831lm 4000K Natural White



Physical Properties	
Width (W)	180 mm
Diameter (D)	180 mm
Height (H)	27.5 mm
Weight	210 g/unit
IP Class	IP50
Carton	20 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	960 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	12.2 kWh/1000hours
AC Current	99 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.54

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	5.58 W
Beam Angle	98°
Luminous Flux	1,831 lm
CRI	85 Ra
Lighting Efficiency	151 lm/W
Color Temperature	4000 K
Color Temperature Name	Natural White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	50°C
Safe to Touch	No

REDEEM PLUS


Downlight C18W 5000 K

With an average efficiency of **153 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC18W502182NN




Light Projection Diagram



D: 180 mm H: 27.5 mm W: 180 mm



Min. 148 mm
Maks. 176 mm
5.83 inch 6.93 inch




Color Spectrum Distribution

REDEEM PLUS


Downlight C18W 5700 K

With an average efficiency of **149 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.


DLRPC18W572182NN




Light Projection Diagram



D: 180 mm H: 27.5 mm W: 180 mm



Min. 148 mm
Maks. 176 mm
5.83 inch 6.93 inch



Color Spectrum Distribution

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC18W502182NN
GTIN (EAN13)	8684216001277
Case	C18
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C18W 5000K
Description	Tuled Redeem Plus Downlight C18W 12.2W 1858lm 5000K Tuled White



Physical Properties	
Width (W)	180 mm
Diameter (D)	180 mm
Height (H)	27.5 mm
Weight	210 g/unit
IP Class	IP50
Carton	20 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	960 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	12.2 kWh/1000hours
AC Current	99 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.54

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	5.70 W
Beam Angle	98°
Luminous Flux	1,858 lm
CRI	85 Ra
Lighting Efficiency	153 lm/W
Color Temperature	5000 K
Color Temperature Name	Tuled White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Equivalent	
Equivalent Incandescent Typical	145 W
Equivalent CFL	29 W
Equivalent LED Bulb	24 W
Tuled	12.2 W
Efficiency Compared to Inc.	1,075 %
Efficiency Compared to CFL	135 %
Eff. Compared to Traditional LED	86 %

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	50°C
Safe to Touch	No

General Info & ID

Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC18W572182NN
GTIN (EAN13)	8684216001284
Case	C18
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C18W 5700K
Description	Tuled Redeem Plus Downlight C18W 12.2W 1819lm 5700K Gloss White



Physical Properties	
Width (W)	180 mm
Diameter (D)	180 mm
Height (H)	27.5 mm
Weight	210 g/unit
IP Class	IP50
Carton	20 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	960 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	12.2 kWh/1000hours
AC Current	99 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.54

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	5.74 W
Beam Angle	98°
Luminous Flux	1,819 lm
CRI	85 Ra
Lighting Efficiency	149 lm/W
Color Temperature	5700 K
Color Temperature Name	Gloss White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No


Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	50°C
Safe to Touch	No

REDEEM PLUS




Downlight C18W 6500 K

With an average efficiency of **148 lm/W**, we have combined energy saving and quality. We offered **seven (7) different color temperature options** to achieve a unique atmosphere in every space.

DLRPC18W652182NN



Light Projection Diagram



General Info & ID	
Product Type	Downlight
Series Name	Redeem Plus
Product Code	DLRPC18W652182NN
GTIN (EAN13)	8684216001291
Case	C18
Case Sub Type	W
Base	2-Pole 2-Pin Spring Terminal
Description	Tuled Redeem Plus Downlight C18W 6500K
Description	Tuled Redeem Plus Downlight C18W 12.2W 1799lm 6500K Cool White



Physical Properties	
Width (W)	180 mm
Diameter (D)	180 mm
Height (H)	27.5 mm
Weight	210 g/unit
IP Class	IP50
Carton	20 (pcs)
Euro Pallet	48 (carton)
Euro Pallet	960 (pcs)

Electrical Characteristic	
Efficiency Class (EU 2019/2015)	D (A-G)
Yearly Consumption	12.2 kWh/1000hours
AC Current	99 mA
Mains Voltage Rate Minimum	110 VAC
Mains Voltage Rate Maximum	240 VAC
Mains Frequency Minimum	40 Hz
Mains Frequency Maximum	60 Hz
Power Factor	0.54

Environmental Features	
RoHs 2011/65/EU Compliant	Yes
Hg Free Compliant	Yes
EAC	Yes
CE	Yes
Recyclable	No
Fragile	Yes
Protected Against Water	No
Safe to Trash	No

Light Characteristic	
Declared Radiant Power	5.78 W
Beam Angle	98°
Luminous Flux	1,799 lm
CRI	85 Ra
Lighting Efficiency	148 lm/W
Color Temperature	6500 K
Color Temperature Name	Cool White

Production Composition	
Driver Type	On Board IC
Body Material	PA - V0
LED Chip Vendor	Samsung / Cree
Diffuser Material	PC - Polycarbonates

Lifetime	
Operating Lifetime Expectancy	20,000 Hours
Life Expectancy	15 Years
Switching Count Expectancy	100,000 On/Off
Warranty	36 Months

Functions	
Dimmable	No

Thermal Character	
Operating Temperature Min	-20°C
Operating Temperature Max	50°C
Surface Temperature	50°C
Safe to Touch	No

The technical data was obtained under 25°C, 230V, and 50Hz test conditions.
Technical data may vary depending on the conditions.



Redeem

Ultra Series

Coming soon to production:
innovation at its finest!

Lighting Revolution

We have brought a new
dimension to light in
lighting. Are you ready for a
journey to the future?

Coming soon!

ti



www.tuled.com.tr

